


DIST	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET NO.	TOTAL SHEETS

**Randell D. Hiatt**  
REGISTERED CIVIL ENGINEER

July 19, 2013  
PLANS APPROVAL DATE


THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.

REGISTERED PROFESSIONAL ENGINEER  
Randell D. Hiatt  
No. CS0200  
Exp. 6-30-15  
CIVIL  
STATE OF CALIFORNIA




**TRANSITION AT BRIDGE COLUMNS**


Concrete Barrier Type 60SF  
See Note 7




**SECTION A-A**



**SECTION B-B**



**SECTION C-C**



**TRANSITION AT SIGN PEDESTAL**

Concrete Barrier Type 60SF  
See Note 7

**NOTES:**

- See Standard Plan A76G for Concrete Barrier Type 60S.
- Contractor options for fill between concrete barrier walls:
  - Place 4" PCC at base between concrete barrier walls.
  - Place 1'-0" of granular material at base between walls.
  - Place granular material from base to bottom of 4" cap.
  - Monolithic concrete with foam blockouts is not permitted.
- Reinforcing steel shall extend continuous through construction joints.
- See "Overhead Sign" plans for sign pedestal elevations on new construction.
- Adjust height of concrete barrier wall on low side of offset or superelevated roadways to provide level grade across top of concrete barrier cap.
- See Overhead Signs Standard Plan Pile Foundation Tables.
- All locations with limited shoulder width available for barrier, see Standard Plan A76F for use of Concrete Barrier Type 60GE.

STATE OF CALIFORNIA  
DEPARTMENT OF TRANSPORTATION  
**CONCRETE BARRIER TYPE 60SF**  
NO SCALE

RSP A761 DATED JULY 19, 2013 SUPERSEDES STANDARD PLAN A761  
DATED MAY 20, 2011 - PAGE 42 OF THE STANDARD PLANS BOOK DATED 2010.

**REVISED STANDARD PLAN RSP A761**