

**INSTRUCTIONS TO FABRICATOR**

**PROJECT PLANS SHOW:**

1. Sign structure location.
2. Length of structure frame.
3. Panel size and locations on structure.
4. Walkway length for two post signs.
5. Post type and height to bottom of frame.
6. Base plate elevation.
7. Footing elevation or location of pile foundation.
8. Photoelectric unit location if required.

REFER TO THE FOLLOWING STANDARD PLANS FOR DETAILS NOT SHOWN ON PROJECT PLANS:

Sheet No.	SHEET NAME
S1	Overhead Signs-Truss, Instructions and Examples
S2	Overhead Signs-Truss, Single Post Type, Post Types II to IX
S3	Overhead Signs-Truss, Single Post Type, Base Plate and Anchorage Details
S4	Overhead Signs-Truss, Single Post Type, Structural Frame Members Details No. 1
S5	Overhead Signs-Truss, Single Post Type, Structural Frame Members Details No. 2
S6	Overhead Signs-Truss, Gusset Plate Details
S8	Overhead Signs-Truss, Single Post Type, Round Pedestal Pile Foundation
S9	Overhead Signs-Truss, Two Post Type, Post Types I-S through VII-S
S10	Overhead Signs-Truss, Two Post Type, Base Plate and Anchorage Details
S11	Overhead Signs-Truss, Two Post Type, Structural Frame Members
S12	Overhead Signs-Truss, Structural Frame Details
S13	Overhead Signs-Truss, Frame Juncture Details
S15	Overhead Signs-Truss, Two Post Type, Round Pedestal Pile Foundation
S16	Overhead Signs, Walkway Details No. 1
S17	Overhead Signs, Walkway Details No. 2
S17A	Overhead Signs, Walkway Details No. 3
S18	Overhead Signs, Walkway Safety Railing Details
S19	Overhead Signs-Truss, Sign Mounting Details, Laminated Panel-Type A
S20	Overhead Signs, Steel Frames, Removable Sign Panel Frames
S21	Overhead Signs, Removable Sign Panel Frames, Mounting Details
S22	Overhead Signs-Truss, Removable Sign Panel Frames, 9'-2" and 10'-0" Sign Panels

**WALKWAY BRACKETS:**

Space all walkway brackets maintaining uniform spacing where possible. Maximum spacing shall not exceed 5'-6".

**LIGHTING FIXTURE SUPPORTS:**

Where distance from walkway bracket to end of sign panel exceeds 1'-4", extend lighting fixture supports to next walkway bracket. See Example No. 2.

**WALKWAY AND SAFETY RAILING:**

Walkway to be continuous for entire length of frame for single post signs. For two post signs, see Project Plans. Safety railing to protect entire walkway, but continuous for no more than 11'-0" in one unit.

**GENERAL NOTES:**

**LOADING:**

**WIND LOADING:**

Normal to face of sign: 40.3 psf on 100% Truss surface area (i.e. 100% panel coverage).  
 Transverse to face of sign: 20% of normal force.

**WALKWAY LOADING:**

Dead load +500 LB concentrated live load.

**UNIT STRESSES:**


STRUCTURAL STEEL:  $f_y = 36,000$  psi  
 REINFORCED CONCRETE:  $f_y = 60,000$  psi  
 $f'_c = 3600$  psi  
 FOOTING SOIL PRESSURE: 2.5 ksf (spread footing)

**MINIMUM CLEARANCE**

Vertical roadway clearance 18'-0" (bottom of walkway system)



**WELDING:**

All welding continuous unless otherwise noted on the plans.




**NOTES:**

1. Signs are shown and dimensioned looking in the direction of traffic. Double faced signs are shown and dimensioned looking ahead along stationing.
2. Mandatory dimension limit.




**UNBALANCED SINGLE POST TYPE**

Example No. 1



**CANTILEVER SINGLE POST TYPE**

Example No. 2



**TWO POST TYPE WITH CANTILEVER (PART DOUBLE-FACED)**

Example No. 3

STATE OF CALIFORNIA  
 DEPARTMENT OF TRANSPORTATION

**OVERHEAD SIGNS-TRUSS INSTRUCTIONS AND EXAMPLES**  
 NO SCALE

RSP S1 DATED JULY 19, 2013 SUPERSEDES STANDARD PLAN S1 DATED MAY 20, 2011 - PAGE 334 OF THE STANDARD PLANS BOOK DATED 2010.

**REVISED STANDARD PLAN RSP S1**

DIST	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET NO.	TOTAL SHEETS

Stanley P. Johnson  
 REGISTERED CIVIL ENGINEER  
 No. CS7933  
 Exp. 3-31-14  
 CIVIL  
 STATE OF CALIFORNIA

July 19, 2013  
 PLANS APPROVAL DATE  
 THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.

TO ACCOMPANY PLANS DATED \_\_\_\_\_

2010 REVISED STANDARD PLAN RSP S1